

Penetrometry in Microgravity Environments

SRR-PTMSS 2014

Colorado School of Mines - Golden, CO
10th - 11th June, 2014

Paul Sánchez and Daniel J. Scheeres
Colorado Center of Astrodynamics Research






University of Colorado **Boulder**

Motivation

- The Hayabusa mission to Itokawa and future sample-return missions (OSIRIS-REx and Hayabusa 2) will have to interact with asteroid surfaces to accomplish their objectives.
- Though much is known about the dynamics of granular aggregates on Earth, micro-gravity environments are largely unknown.
- The mechanisms need to be tested before they are used, but the right gravitational conditions cannot be readily obtained experimentally on Earth.


First Impact

- The same experiment with 3 different gravitational fields.
- Impact velocity $\sim 10\text{cm/s}$.





Paul Sánchez, PhD, Research Associate.

Soft-Sphere DEM



Paul Sánchez, PhD, Research Associate.


TAGSAM-OSIRIS-REx



Will the geometry of the sampler chamber capture
or not the regolith upon impact?

Paul Sánchez, PhD, Research Associate.


Typical Simulation



Polydisperse regolith: 0.5-2.5 cm
Hemisphere radius: 0.45 m
Impact speed: 0.2 m/s


Paul Sánchez, PhD, Research Associate.

Sampler Head and Chamber




- Detail of the sampler head as it was implemented for simulations.
- The snapshots show the particles getting into the sampler chamber at the beginning of the simulation.
- The rest of the simulations shows them staying inside it.


$v_i = 15 \text{ cm/s}$




$t = 0.1 \text{ s}$



$t = 0.2 \text{ s}$




$t = 0.3 \text{ s}$



$t = 0.4 \text{ s}$

Paul Sánchez, PhD, Research Associate.


Velocity Profile (upper layer)



- There will always be regolith coming up towards the space-craft, but its velocity depends on the mass of the impactor.
- The upward velocity of the regolith is close to the impact velocity of the cylinder.

Paul Sánchez, PhD, Research Associate.

Sampler Head and Chamber: Remarks



- The peaks in the force “felt” by the sampler head corresponds to the instants of contact between the flat a surface and the regolith.
- The height of the peaks depends directly on the impact velocity. This was also confirmed for higher impact velocities.

Paul Sánchez, PhD, Research Associate.


Drag Force at 1 μ g

- The plot shows the force that the sampler would “feel” during the first impact with the regolith without the influence of the spring.
- The gravity field has been adjusted to 1 μ g.
- The horizontal lines show a V_i^2 proportionality of this force.
- This finding could point to a liquid-like behaviour of the regolith under these low-gravity conditions.
- Proportionality indicates high Reynolds number drag:





$$\frac{1}{2}\rho V_i^2 C_D A$$

- Physically this makes sense as the regolith “fluid” reacts in turbulent-like fashion.

Paul Sánchez, PhD, Research Associate.



Other Gravitational Fields ($v_i=10$ cm/s)



The force that the mechanism feels remains independent of the gravitational field up until $100\mu g$ and then it begins to change.

Paul Sánchez, PhD, Research Associate.

Cohesive Regolith

Paul Sánchez, PhD, Research Associate.








University of Colorado
Boulder



Celestial and Space Flight
Mechanics Laboratory


Lowest point of penetration




Paul Sánchez, PhD, Research Associate.

Position and Velocity

Position of the Sampler Head vs. Time



Vertical Velocity of the Sampler Head vs. Time




Paul Sánchez, PhD, Research Associate.

A different projectile


Paul Sánchez, PhD, Research Associate.

Non-spherical projectile (Cone)

- For the following simulations we are using a Soft-sphere DEM code.
- This code simulates the dynamics of 180.000 spherical grains as they are impacted with a right circular cone.
- **Gravity field:** external gravitational field of $1\mu\text{G}$
- **Grains:**
 - Size distribution: **a.** 0.9 - 1.1 cm; **b.** 0.5-2.5 (1/d).
 - Static and dynamic friction are implemented.
 - Material density: 2500 kg/m^3 .
 - Packing fraction: **a.** 0.62; **b.** 0.64.
- **Cone:**
 - Material density: 8000 kg/m^3 .
 - Height: 6 cm.
 - Radius: 1.6 cm.
 - Impact speed: 10, 30, 50, 70 and 90 cm/s
- **Container:** hemisphere, 45 cm radius.
- **Simulation time:** 10 s.




Typical Simulation



Monodisperse material: ~1cm
Impact velocity: 90cm/s
Total time:10 s

Paul Sánchez, PhD, Research Associate.


Velocity Profile (upper layer)



- There will always be regolith coming up towards the space-craft, but its velocity depends on the mass of the impactor.
- The upward velocity of the regolith is about one order of magnitude smaller.

Paul Sánchez, PhD, Research Associate.

Normalized Speed



Paul Sánchez, PhD, Research Associate.

Conclusions

- For values of the gravitational field in the micro-gravity regimen, the resistance force on the TAGSAM is independent of its impact velocity.
- Both impactors always produce regolith that moves “upwards” and that could potentially impact the space-craft.
- The upwards velocity of this regolith depends on the mass of the impacting body and its shape.
- The size range of the regolith did not produce a noticeable change in the dynamics of the TAGSAM; however, this was not the case for the cone where its displacement was shortened.
- The drag force on the cone and the sampler head upon impact show a dependence on v^2 .

Thanks, any questions?

Paul Sánchez, PhD, Research Associate.