



Autonomous Digging

Reducing the impact of
communications delay
for planetary mining

8/19/15


Andrew Dobson
Clearpath Robotics, Kitchener

Dr. Joshua Marshall
Queen's University Mining Systems Lab

CIM PTMSS 2015 Montreal, Abstract 763



Remote Loading



ESA 2014 [1]





Robotic Loading






Key Results

Manual Bucket Valve Command Characteristics






Communication Delay





Communication Delay





The diagram illustrates the communication environment between Earth and the Moon. At the bottom is a blue bar representing Earth. Above it is a grey bar representing the Moon. A blue satellite is positioned on the Moon's surface. A red vertical rectangle represents a ground station on Earth. Three horizontal dashed lines represent different communication links: EM L2 (top), EM L1 (middle), and GEO (bottom). A solid black line connects the satellite to the ground station, with a label '~ 0.4 s round trip [3]' next to it. A dotted black line connects the satellite to the ground station, with a label '~ 0.8 s round trip' next to it.

EM L2

~ 0.4 s round trip [3]

Moon

~ 0.8 s round trip

EM L1

- 150 m/s per year Δv [4]
- Real time telepresence limit ~ 0.3 to 0.5 s [5, 4]
- Expensive humans
- Squishy humans
 - Limited endurance
 - Beyond Earth's magnetic field
 - Galactic cosmic ray exposure risk [3]

GEO

Earth



Overcoming Delay

- Prediction
 - Displays [5, 6, 7]
 - Virtual environment(s) [8, 9]
 - Force feedback and bilateral control [10, 11]
 - Compliance control
 - Contact force controlled locally increasing delay error tolerance [5, 6]
 - Move and wait [5, 7, 12]
 - Automation and supervisory control [7, 12]
- $< 2 \text{ s}$ [7]
- $> 10 \text{ s}$ [7]



Test Platforms






Algorithm

1. Go to entry pose
2. Detect entry
3. Activate admittance controller
 - Control admittance between bucket and pile
 - Automatically avoid force concentrations

$$v = k \cdot (f \downarrow T - f \downarrow S)$$

4. Detect maximum bucket curl
5. Go to weighing pose





Why Auto Load on Earth?

- Productivity
 - Automate the entire LHD cycle
 - ↑ productivity [14]
 - ↑ consistency [15]
 - Turn all operators into expert operators [15]
- Reduce safety costs
 - Distance operators from worksite [16]
 - Work more hazardous stopes [17]
 - Increased sensing [18]
- Reduce operating costs
 - Tune loading to match hauling equipment [19]
 - More predictable consumable consumption [17, 19]





Previous Attempts

- Scripted controllers
 - Several patents
 - Only works in homogeneous targets
 - Most notable: Caterpillars AutoDig system [20]
- Behaviour and fuzzy logic
 - Based on experimentally derived heuristics
 - Unpredictable results when conditions change
 - Most notable: Lever and Shi's CAT 980G work [21]
- Force feedback controllers
 - Impedance \leftarrow better for target shaping
 - Admittance \leftarrow better for bucket filling





Force Control

- Impedance (Z)
 - $f = Z \cdot (v - v \downarrow t)$
 - Requires a target **velocity or path**
 - Most notable: Maeda et al. [22]
- Admittance (Y)
 - $v = Y \cdot (f - f \downarrow t)$
 - Requires a target **force**
 - Most notable: Marshall et al. [23]
Seraji [24]







MSL Results



S vs $PI \rightarrow t \downarrow d \uparrow 55\%$, $M \downarrow d \uparrow 18\%$, $W \downarrow d \uparrow 26\%$



ST14 Results



Man vs Auto $\rightarrow t \downarrow d \downarrow 39\%$, $M \downarrow d \uparrow 39\%$, $W \downarrow d \uparrow 68\%$




ST14 Typical



Controller:

$$v \downarrow A = k \downarrow A \cdot e \downarrow f$$


$$v \downarrow A = k \downarrow A \cdot (f \downarrow T - f \downarrow S)$$






Manual vs Admittance

Manual



P 11 MN





Results and Contributions

- Why automate
 - Cost
 - Communications delay increases task time
 - Minimum delay 0.4 s
 - Mean manual digging command period ~ 1.6 s
- Productive and consistent loading algorithm
 - Dig time ($t \downarrow d$) \downarrow 39%
 - Payload ($M \downarrow d$) \uparrow 39%
 - Work ($W \downarrow d$) \uparrow 68%
- Applicable to multiple vehicles and environments
- ST14 FSR2015 Paper: [24]



Thank You



This research was also supported in part by the Natural Sciences and Engineering Research Council of Canada (NSERC) under grant 371452-2009.



References



-
- [1] ESA Foster+Partners, November 2014, [Online]. Available: http://www.esa.int/spaceinvideos/Videos/2014/11/3D-printing_a_lunar_base
 - [2] J. R. Carpenter, D. Folta, M. Moreau, and D. Quinn, "Libration Point Navigation Concepts Supporting the Vision for Space Exploration," AIAA, 16-19, 2004.
 - [3] J. Burns et al., "A lunar L2-Farside exploration and science mission concept with the Orion Multi-Purpose Crew Vehicle and a teleoperated lander/rover," in Advances in Space Research, Vol. 52, 2013, pp. 306-320.
 - [4] D. F. Lester, H. A. Thronson, "Human space exploration and human spaceflight: Latency and the cognitive scale of the universe." Space Policy 27, 2011 89–93.
 - [5] T. Sheridan, "Space teleoperation through time delay: review and prognosis." Robotics and Automation, IEEE Transactions on 9, no. 5, 1993, pp. 592-606.
 - [6] A. Bejczy, W. Kim, "Predictive Displays and Shared Compliance Control for Time- Delayed Telemanipulation," in IROS, 1990. Proceedings, IEEE International Workshop on Intelligent Robots and Systems, 1990, pp. 407-412.
 - [7] K. Hambuchen, R. Burrige, and W. Bluthmann, "Forming human-robot teams across time and space," GLEX, 2012.
 - [8] L. Huijun, and A. Song, "Virtual-environment modeling and correction for force-reflecting teleoperation with time delay," Industrial Electronics, IEEE Transactions on 54.2 2007, pp. 1227-1233.
 - [9] R. Winck, S. Sketch, E. Hawkes, D. Christensen, H. Jiang, M. Cutkosky, and A. Okamura, "Time-delayed teleoperation for interaction with moving objects in space." In Robotics and Automation (ICRA), IEEE International Conference on, 2014, pp. 5952-5958.
 - [10] T. Kotoku, "A predictive display with force feedback and its application to remote manipulation system with transmission time delay." Intelligent Robots and Systems, Proceedings of the 1992 IEEE/RSJ International Conference on. Vol. 1. IEEE, 1992.
 - [11] C. Preusche, D. Reintsema, and G. Hirzinger, "Robotics component verification on iss rokvisss-preliminary results for telepresence." Intelligent Robots and Systems, IEEE/RSJ International Conference on. IEEE, 2006.
 - [12] T. Fong, M. Diftler, and D. Mittman, "The Human Exploration Telerobotics Project: Objectives, Approach, and Testing," In Aerospace Conference, IEEE, 2012 pp. 1-9.



References (cnt)



-
- [13] J. Donovan, "Underground automation: Key learnings review," Barrick, Toronto ON., Report, March 2008.
 - [14] P. Lever, R. Pakalnis, P. Hughes, R. Pakalnis, P. Hughes, C. Brannon, G. Carlson, and T. Casten, SME Mining Engineering Handbook, 3rd ed., P. Darling, Ed. Society for Mining, Metallurgy, and Exploration Inc. (SME), 2011.
 - [15] D. R. Wilburn, R. L. Vasil, and A. Nolting, "Exploration review," Mining Engineering, vol. 63, no. 5, 2011.
 - [16] A. Gustafson, H. Schunnesson, D. Galar, and U. Kumar, "Production and maintenance performance analysis: manual versus semi-automatic lhds," Journal of Quality in Maintenance Engineering, vol. 1, no. 19, pp. 74 { 88, January 2013.
 - [17] J. Larsson, "Unmanned operation of Load-Haul-Dump vehicles in mining environments," Masters, Orebro University, Orebro Sweden, November 2011.
 - [18] A. Uzbekova, A. Clement, E. Mort, G. Smith, and R. Butcher, "Kanowna belle minegem trial report," Barrick Gold of Australia, Caterpillar and WesTrac, Level 10, 2 Mill St. Perth WA 6005, Report, November 2010.
 - [19] Caterpillar, "Wheel loaders: Aggregate autodig operator tips: video," Caterpillar Safety Services, Accessed October 2014 2002, [Online]. Available: <https://safety.cat.com/cda/layout?m=129939&x=7&id=496053>
 - [20] X. Shi, P. Lever, and F. Wang, Autonomous Rock Excavation: Intelligent Control Techniques and Experimentation, ser. Series in intelligent control and intelligent automation. World Scientific, 1998.
 - [21] G. J. Maeda, D. C. Rye, and S. P. N. Singh, "Iterative autonomous excavation," in Field and Service Robotics, ser. Springer Tracts in Advanced Robotics, K. Yoshida and S. Tadokoro, Eds. Berlin Heidelberg Germany: Springer Berlin Heidelberg, 2013, vol. 92, pp. 369-382.
 - [22] J. Marshall, "Towards autonomous excavation of fragmented rock: Experiments, modelling, identification and control", Master of Science: Engineering, Queen's University, Kingston, On. Canada, August 2001.
 - [23] H. Seraji, "Adaptive admittance control: an approach to explicit force control in compliant motion," in Robotics and Automation, 1994. Proceedings., 1994 IEEE International Conference on, vol.4, 1994, pp. 2705-2712.
 - [24] A. Dobson, J. Marshall, J. Larsson, "Admittance Control for Robotic Loading: Underground Field Trials with an LHD" in Field and Service Robotics 2015, Toronto ON., no 7, June 2015.




Next?





Future work

- Working mine → Production data set
- Digging model → offline tuning
- Auto dig study → dig planner design





Experimental Method

- Goal was always dig efficiency not controller stability
- Access to real hardware (reduced need for modelling)
- Typical field research issues
 - Sourcing
 - Qualification
 - Calibration
 - Breakdowns
 - Weather
 - Comms





Muck Piles





ST14 Consistency

Mass

Time

Work

