



SpaceTReX




ISRU of Water for Interplanetary Steam Propulsion using Carbon Nanoparticles

Nathan Barba, Salil Rabade, Jekan Thangavelautham
Space and Terrestrial Robotic Exploration (SpaceTReX) Laboratory
School of Earth and Space Exploration
Arizona State University




SpaceTREX

Space and Terrestrial Robotic Exploration Laboratory




Motivation – Interplanetary Exploration




MARCo [JPL]



Swirl
[ASU/JPL/APL/Busek/Kinetix]




LunaH-Map
[ASU/JPL/RMD/Busek/Kinetix]





INSPIRE [JPL]



Longmier [U. of Michigan]



Planetary Surface Exploration/Prospecting





Need for a Sustainable Propulsion System

- High or good-enough delta V
- Long storage life, minimal thermal footprint
- High thrust – particularly for capture burns.
- Low-storage risk, safety
- Propellants that are compatible with ISRU methods
- Ease of refueling




Water Steam vs. Water Electrolysis

- We are pursuing both approaches.
- Focus here will be water steam and we will compare against water electrolysis



Water Steam Propulsion

- Properties of steam well understood
 - Minimal storage risk
- Isp up to 200 s
 - Generated from super heated steam, +1500 C
- Use of carbon nanoparticles to heat the water using solar thermal concentrator.
 - Free power sources, up to 99 % of sunlight can be converted to heat.




Steam Propulsion

- Achieve high temperatures with low-fidelity concentrator
- Compact, solid-state heating platform
- Comparably high thrust force compared to electrical propulsion methods.



Steam Propulsion


- Comparable in Isp to mono-props
- Compatible with ISRU methods to extract water from Deimos/Phobos, asteroids, Moon.
- Probably not a solution for Mars






Steam Propulsion

- Steam propulsion is not a new concept.
- Old concepts required fission reactors, were meant to be large tug-boats of cis-lunar space.





Steam Generation Using Carbon Nanoparticles



Source: "Solar Vapor Generation Enabled by Nanoparticles" Halas, et al. 2013

- Concentrated light absorbed due to sub-wavelength geometry.
- Particles resonate, collect and transfer energy as heat.



Steam Generation Using Carbon Nanoparticles

- Carbon Black N115, 82-86 % absorptivity
- Vanta Black, 99.5 % absorptivity



Carbon Black N115




Vanta Black




Steam Generation Using Carbon Nanoparticles

- These nanoparticles may naturally occur on asteroids.
- Heating occurs on a molecular scale. Very precise and local.
- Some of this maybe a challenge for in space-propulsion.



Laboratory Experiments






Initial Tests





Concentrator Test Results

- Time for wood to catch fire: ~5-7 seconds
- Time for 15 ml of distilled water to boil: 10 minutes got upto 100°C
- Steam was evident ~5.5min






Early Results with Carbon Nanoparticles



- Solar to heat conversion efficiency: 82 %

Condition	Time to Boil	Deviation
Distill Water	600 sec	10 %
Distill Water + Nanoparticles	40 sec	15 %

- Up to 15x shorter time to boil.



Early Results with Carbon Nanoparticles







Solar Thermal Steam Propulsion Concept


Components	Mass (kg)	Volume (L)
Propellant	7	7
Propulsion Dry Mass	3	1
Comms & ACDS	2	1
Structure	1	0.5
Power	1	0.5

- **Aggressive, optimized design.**
- **Delta V = 1400 m/s vs. 2500 m/s for Photovoltaic Electrolysis.**




Solar Thermal Spacecraft Concept






Solar Thermal Spacecraft Concept






Inflatables


- Few grams of solid powder inflates parabolic antenna, UV resin cures inflatable into shape.
- Further enhancements can pave the way for a solar thermal concentrator



[Babuscia, Chandra, Thangavelautham 2016]

PV Electrolysis Spacecraft Concept





System Performance


- For short pulses
 $I_{sp} = 360s$
- For a 6U CubeSat
 - Total Mass – 14 kg
 - Dry Mass – 4.5 kg
 - $\Delta V = 4000 \text{ m/s}$

To	Required ΔV
Low Lunar Orbit	4040 m/s
EML – 1	3770 m/s
EML - 2	3430 m/s




PV Electrolysis Spacecraft Concept

- Concept developed based on currently available state of the art CubeSat components
- PEM Electrolyzer with 85-90 % conversion efficiency
- Dual-body design, lower stage is centrifuge to separate water from the propellants.




System Operation



→ Water
→ Electrolyzed H₂


Side View of
PVEPS




Lower segment rotates to separate
water from reactants



General Case & Electrolysis Comparison






Discussion

- Overall, solar-thermal steam propulsion system is simpler, but at the cost of reduced performance
- Well aligned with a water-based cis-lunar economy concept.
- Water can be with impurities, particularly sulfur, carbon monoxide
- Easier adoption, until advancements make electrolysis options more practical.

SpaceTREx Team







AOSAT I



SWIMSat



SunCube FemtoSats



SpaceTrex

Adventure Awaits

