



Self-Propagating Chemical Reactions for Making Materials and Structures from Lunar and Martian Regolith

Evgeny Shafirovich and Robert Ferguson

The University of Texas at El Paso

Ninth Joint Meeting of Space Resources Roundtable and Planetary & Terrestrial Mining Sciences Symposium
June 12 – 15, 2018, Golden, CO

Why Do We Need Materials/Structures There?


- Habitats, radiation shielding
- Launch/landing pads
- ...



Lunar base made with 3D printing.
Credit: ESA/Foster + Partners

How to Make Materials/Structures There?

- Bring everything from Earth.
- Use only local materials with energy obtained from a nuclear reactor or (if there is enough sunlight) solar arrays.
- Use mainly local materials with a small amount of materials brought from Earth and a small amount of energy.
 - Exothermic reactions release heat, which may make the process self-sustained.



Schematic of Combustion Synthesis






What Reactions?

- Inert regolith and reactive mixture
 - Intermetallics: Ti/B, Al/Ni, ...
 - Thermites: Al/Fe₂O₃, Al/FeTiO₃, ...
- Regolith + metal (thermite reaction)
 - Al – hard to ignite, needs an additional component e.g., polytetrafluoroethylene (PTFE)
 - Mg – easy to ignite



Combustion of Regolith with Magnesium

- Milling regolith
- Mixing with Mg
- Compacting to a pellet
- Igniting the pellet





How Does It Burn?



JSC-1A/Mg (23 wt% Mg)
Coarser regolith



JSC-1A/Mg (26 wt% Mg)



Mojave Mars/Mg (30 wt% Mg)



JSC-Mars-1A/Mg (30 wt% Mg)

10 wt% Mg was needed for a self-sustained combustion of JSC-1A

How Does the Product Look?

Original JSC-1A/Mg pellet

After combustion in Ar


After combustion followed by compaction






What Did React with Mg?



Compound	Concentration, wt%		
	JSC-1A [6]	JSC-Mars-1A [7]	Mars Mojave [7]
SiO ₂	45.7	43.48	49.4
Al ₂ O ₃	16.2	22.09	17.1
Fe ₂ O ₃	12.4	16.08	10.87
CaO	10.0	6.05	10.45
MgO	8.7	4.22	6.08
Na ₂ O	3.2	2.34	3.28
TiO ₂	1.9	3.62	1.09



Differential scanning calorimetry
Mg – SiO₂ – Fe₂O₃ mixtures



Differential scanning calorimetry
Mg – Regolith simulant mixtures



JSC-Mars-1A has the highest content of Fe₂O₃.
It burns more vigorously.

The higher SiO₂-Fe₂O₃ ratio, the lower the peak temperature.
SiO₂ facilitates the ignition.



Conclusions on Regolith–Mg Combustion

- Mixtures of lunar and Martian regolith simulants with Mg exhibit a self-sustained combustion, leading to formation of ceramic materials.
- Without preheating, 10 wt% Mg was needed for a self-sustained combustion of JSC-1A.
- The reaction mechanisms in these mixtures involve thermite reactions of Mg with iron oxide and silica.
 - Iron oxide ensures intensive combustion.
 - Silica facilitates the ignition.



Regolith Tiles for Launch/Landing Pads

- Kennedy Space Center makes regolith tiles.
- The tiles can be laid down and interlocked, but this is not reliable.
- Solution: Place a reactive mixture between the tiles and ignite it to weld the tiles.
 - Thermites?
 - Intermetallics?






Assembling a launch/landing pad.
Credit: PISCES



Al-Ni Combustion for Joining Regolith Tiles

- Cutting tiles
- Mixing Al and Ni
- Installation in a holder and shaking
- Installation in a vacuum chamber
- Making 10 mbar Ar environment
- Igniting the mixture






How Does It Burn?





Combustion Front Velocity *versus* Distance

- Modelling
- Properties determined
 - Density
 - Specific heat
 - Thermal diffusivity
 - Thermal conductivity
- Reasonable correlation
- Small quenching distance



The combustion front velocity vs. the distance between the tiles. Calculations at different values of the adiabatic combustion front velocity (8, 9, and 10 mm/s) and different thermal diffusivities. Black: Experimental values



Joining?



Joining is occurring but is not consistent.





Conclusions on Combustion Joining of Tiles

- Experiments on combustion of Al/Ni mixture in 2–8 mm gap between two JSC-1A tiles have been conducted in Ar at 10 mbar.
- Stable propagation of the combustion front was observed.
- The quenching distance is low (< 2 mm in the experiments).
 - A small amount of the reactive mixture would be required for joining regolith tiles on the Moon.
- Joining of the tiles was achieved in some experiments.
 - A better mixture is needed to increase the temperature.
 - A better holder is needed to fix the thermal expansion problem.

Concluding Remarks



- When energy is limited, a self-propagating exothermic reaction (combustion synthesis) is a promising solution.
- It can:
 - make useful materials
 - join parts
 - generate heat





Acknowledgments

- NASA
Minority University Research Education Project
Dr. James Mantovani of Kennedy Space Center
- Students
Francisco Alvarez
Sergio Cordova
Armando Delgado
Robert Ferguson
Ashvin Kumar Narayana Swamy
Christopher White



Thank you!