

“Commercialization and Human Settlement of the Moon and Cislunar Space using ISRU, Fission Surface Power, and Advanced In-Space Propulsion Systems”

Stan Borowski (NASA/GRC – retired)

Steve Ryan (NASA/GRC)

Dave McCurdy (Vantage Partners, LLC at GRC)

Bob Sauls (XP4D, LLC)

e-mail: sborowski@wowway.com

presented at the

**SRR & PTMSS 10th Joint Meeting
Colorado School of Mines
Golden, Colorado**

June 11 – 14, 2019

Glenn Research Center

SRR & PTMSS 10th Joint Meeting, Golden, Colorado, June 11 - 14, 2019


at Lewis Field




Lunar Trip Images from *2001: A Space Odyssey*

(Image Credits: Stanley Kubrick and Arthur C. Clarke, Metro-Goldwyn-Mayer, 1968)

Orion III Synchronizes Approach to Rotating Space Station V




Space Station V – Rotation radius, rate, and AG level: 150 m, 1 rpm, and 1/6th g



Orion III Commercial ETO Spaceplane



Aries-IB Moon Shuttle
Descends to Clavius base



Aries-IB Touchdown



Glenn Research Center

SRR & PTMSS 10th Joint Meeting, Golden, Colorado, June 11 - 14, 2019

at Lewis Field



Introduction and Presentation Overview

- Over 50 years have passed since the movie *2001: A Space Odyssey* debuted in April, 1968.
- In the film, Dr. Heywood Floyd flies to a large artificial gravity space station orbiting Earth aboard a commercial space plane. He then embarks on a commuter flight to the Moon arriving there ~25 hr later.
- Today, on the 50th anniversary of the Apollo 11 lunar landing, the images in *2001* remain well beyond our capabilities and *2100: A Space Odyssey* seems a more appropriate title for Kubrick & Clarke's film.
- This presentation looks at key technologies, systems, and supporting infrastructure
 - In-situ resource utilization (ISRU) – using polar icy regolith and volcanic glass as feedstock;
 - Fission power systems (FPS) – to supply abundant “24/7” power on the lunar surface and in orbit;
 - Advanced in-space propulsion systems – allowing bipropellant LO₂/LH₂ operation; and
 - Space transportation nodes (STNs) – provide convenient staging locations in LEO, LPO, and LLO

that could be developed by NASA and the private sector over the next several decades that could allow the operational capabilities presented in *2001* to be achieved, albeit on a more “spartan scale”.

- A reusable, space-based lunar transportation system (LTS) that uses lunar-derived propellants (LDPs) and operates between STNs/depots located in LEO, LPO and LLO is examined.
- Included in the analysis are the LDP production, mining, and power requirements that also include the needs of the LLVs supporting a particular mission type (e.g., crew cargo transport or commuter shuttle).
- A comparison of the requirements using icy regolith and volcanic glass as feedstock materials is included and the synergy with an evolving helium-3 mining industry is also discussed.



Glenn Research Center

at Lewis Field



Extracting Water Ice from Permanently Shadowed Craters in the Moon's Polar Regions will be Extremely Challenging

- LPI deposits are important because they could supply both oxygen and hydrogen provided they can be economically accessed, mined, processed and stored for their desired use.
- Higher ΔV s are required to access LPO sites and the candidate craters are deep, extremely cold, and exist in a state of perpetual darkness posing major challenges for the mining and processing of this cold, ice-cemented regolith material.
- The world's 10 coldest mines are located in Russia's extreme northeastern territory. At the coldest of these mines, Sarylakh, the temperatures can drop to nearly -50 C ($\sim 223\text{ K}$).
- By contrast, the temperatures inside the polar craters, where the LPI is thought to exist, are $\sim 30 - 50\text{ K}$ – more than 5x colder than the coldest mines on Earth! At these temperatures, metals can become brittle.
- Conventional mining requires break up, excavation and transport of the ice-bearing regolith to the water extraction plant. It must also operate in a hard vacuum and be able to tolerate the abrasive nature of the lunar dust.
- With in-situ thermal mining*, heat is applied to the regolith surface using directed sunlight, or subsurface, via heating elements, producing sublimated water vapor within a tent enclosure. The vapor is then vented into “cold trap” ice haulers for transport to a central processing plant.
- The water is then purified and electrolyzed for propellants used by LLVs, or shipped to an orbiting propellant depot for electrolysis there.



*D. Kornuta, et al., Commercial Lunar Propellant Architecture – A Collaborative Study of Lunar Propellant Production (2018)


Glenn Research Center

SRR & PTMSS 10th Joint Meeting, Golden, Colorado, June 11 - 14, 2019


at Lewis Field



Volcanic Glass from the Apollo 17 Mission to Taurus-Littrow is Attractive for LUNOX Production



The best lunar oxygen ore found during the Apollo Program is the volcanic glass, found at Taurus-Littrow. The glass beads are fine grained and ~40 mm in diameter. The orange beads are clear glass, while the black beads cooled at bit more slowly and had a chance to crystallize.



Oxygen yield is directly related to iron abundance for the full range of soil compositions. Highest yields are from "FeO-rich" volcanic glass.

Oxygen production from "FeO-rich" volcanic glass is a 2 step process:
 $\text{FeO} + \text{H}_2 \rightarrow \text{Fe} + \text{H}_2\text{O}$ (Hydrogen Reduction & Water Formation)
 $2 \text{H}_2\text{O} \rightarrow 2\text{H}_2 + \text{O}_2$ (LUNOX) (Water Electrolysis & Hydrogen Recycling)



Ref: Carlton Allen, et al., "Oxygen extraction from lunar soils and pyroclastic glass", *J. Geophysical Research*, Vol. 101, No. E11, pgs. 26,085 – 26,095, Nov. 25, 1996

Glenn Research Center


at Lewis Field



Megawatt Electric-class Fission Power Systems are a Key Technology for the Development of Activities in Cislunar Space and on the Moon



Megawatt-class Lunar FPS with Surface Radiator Panel
– Number of units will depend on mining production rates



- MW_e-class fission power system (FPS) has 3 major elements:
- 1) Twin liquid metal-cooled, fast-spectrum reactors using highly enriched U-235 in a uranium nitride fuel form;
 - 2) Dynamic conversion with 4 Brayton TAC units and He-Xe working gas, combined with an AC PMAD system and;
 - 3) Deployable, fold-out radiator system for heat rejection. It uses a liquid NaK pumped loop fluid system combined with lightweight sodium heat pipe radiator panels.

Ref: Human Exploration of Mars Design Reference Architecture 5.0, NASA-SP-2009-566-ADD2, pp. 136-138, March 2014

Propulsion Options: RL10B-2 LO₂/LH₂ Chemical Rocket and Nuclear Thermal Rocket (NTR) Engine




RL10B-2 Chemical Rocket Engine

Performance Parameters:

- Propellants / MR: LO₂ & LH₂ at 5.88:1
- Engine Cycle: **Expander**
- Thrust Level: **24.75 klb_f**
- Exhaust Temperature: **~3000 K**
- Chamber Pressure: **640 psia**
- Nozzle Area Ratio: **280:1**
- Specific Impulse (I_{sp}): **~465.5 s**
- Engine Power Level: **~251 MWt**
- F/W_{eng} : **~37.3**

Ref: Aerojet Rocketdyne RL10 Engine Specifications
@ www.rocket.com (March 2019)



Small Nuclear Rocket Engine (SNRE)

Performance Parameters:

- Propellant: LH₂
- Engine Cycle: **Expander**
- Thrust Level: **16.5 klb_f**
- Reactor Exit Temperature: **2734 K**
- Chamber Pressure: **1000 psia**
- Nozzle Area Ratio: **300:1**
- Specific Impulse (I_{sp}): **~900 s**
- Reactor Power Level: **~365 MWt**
- F/W_{eng} : **~3.03**


Ref: S. K. Borowski, et al., "Affordable Development and Demonstration of a Small NTR Engine: How Small is Big Enough?", AIAA-2015-4524; and NASA/TM—2016-219402

Glenn Research Center




“LO₂-Augmented” NTR (LANTR) Concept: Operational Features and Performance Characteristics

LANTR adds an O₂ “afterburner” nozzle and O₂-rich GG feed system to a conventional NTR engine that provides a variable thrust and Isp capability, shortens burn times, extends engine life, and allows bipropellant operation



LANTR Schematic



Aerojet / GRC Non-Nuclear
O₂ “Afterburner” Nozzle Test*

O/H Mixture Ratio	0	1	2	3	4	5
Delivered Isp (s)	900**	725	637	588	552	516
Thrust Augmentation Factor	1.0	1.611	2.123	2.616	3.066	3.441
Thrust (lb _f)	16,500	26,587	35,026	43,165	50,587	56,779
Engine Mass (lb _m)	5,462	5,677	5,834	5,987	6,139	6,295
Engine T/W	3.02	4.68	6.00	7.21	8.24	9.02


** Fuel Exit Temperature (T_{ex}) = 2734 °K , Chamber Pressure = 1000 psia and NAR = 300 to 1



Growth Missions and Faster Trip Times are Possible using Space Transportation Nodes (STNs) with Refueling Capability

Over time we envision the development of a totally space-based LTS with different types of LTVs operating between STNs located in LEO, equatorially LLO and LPO. The STN provides a propellant depot and cargo transfer function and offers a convenient staging location where propellant, cargo and passengers can be dropped off and/or picked up.

One-way transit times to and from the Moon on the order of 72 hours would be the norm initially. As lunar outposts grow into settlements staffed by visiting scientists, engineers and administrative personnel representing both government and private ventures, more frequent flights of shorter duration could become commonplace.




Cutting the Earth-Moon transit times in half to ~36 hours will require the mission's total ΔV budget to increase by ~25% – from ~8 to 10 km/s. For 24 hour LEO to LLO transit times the total mission ΔV increases by ~62.5% – from ~8 to 13 km/s.

Conestoga – A Reusable Space-based Crew Cargo Transport uses LANTR Engines, a Common NTPS and In-line LO₂ Tank Assembly



Image Credit: Landis Valley Village & Farm Museum, PA

Conestoga Wagons, the “Ships of Inland Commerce,” Transported Settlers, Farm Produce, and Freight across Pennsylvania and Neighboring States for over 150 years



Conestoga-class CCTs may become the “Ships of Cislunar Commerce” in the 2nd half of the 21st Century

Image Credit: NASA/GRC




Image Credit: NASA/GRC

Glenn Research Center

at Lewis Field



Conestoga – LANTR-propelled Crewed Cargo Transport uses a “Common” NTPS and In-Line LO₂ Tank Assembly

CCT delivers **20 t** of cargo; refuels with LDPs

(LEO → LPO → LEO)

- **72-hr “1-way” transit times***
- Total Mission ΔV ~8.378 km/s
- Habitat Module w/4 people ~10.8 t
- Star Truss (**16 m**) w/20 t Payload ~31.5 t
- In-line LO₂ tank element ~71 t
- Common LH₂ NTPS ~ 73 t
- **IMLEO ~186.3 t**
- Return PL ~250 kg
- TLI: MR/lsp~2.6/604 s; LOC:~0.5/804 s; TEI:~5.0/516 s; EOC:~3.9/557 s
- **Total Mission Burn Time: ~29.7 min**

NOTE: CCT refuels with LLO₂ and “tops off” its NTPS with excess LLH₂ from water electrolysis at 8:1 ratio

NTPS carries ~**39.8 t** LH₂ in its 7.6 m OD x ~15.7 m L tank at TLI

“Top off” LLH₂ added to NTPS before TEI ~**6.8 t**

In-line LO₂ tank assembly can carry up to ~**111.2 t** of LO₂ in its 4.6 m OD x ~7.95 m L tank. It carries ~**62.2 t** of LO₂ at TLI and refuels with ~**54.4 t** of LLO₂ in LPO before returning to Earth




Image Credit: NASA/GRC

Glenn Research Center

SRR & PTMSS 10th Joint Meeting, Golden, Colorado, June 11 - 14, 2019

*NOTE: 1-way transit times shown do not include the 2.5-hr long, 3-burn LOC maneuver into LPO

at Lewis Field



An Alternative Propulsion Option for *Conestoga* uses 3 – 24.75 klb_f RL10B-2 LO₂ / LH₂ engines*

CCT delivers 20 t of cargo; refuels with LDPs

(LEO → LPO → LEO)

- 72-hr “1-way” transit times*
- Total Mission ΔV ~8.490 km/s
- Habitat Module w/4 people ~10.8 t
- Star Truss (16 m) w/20 t Payload ~28.2 t
- In-line LO₂ tank element ~111.7 t
- Common LH₂ PS ~ 41.7 t
- IMLEO ~192.4 t
- Return PL ~250 kg
- RL10B-2: MR / Isp~ 5.88:1 / 465.5 s
- Total Mission Burn Time: ~42.2 min

NOTE: CCT refuels with LLO₂ and “tops off” its NTPS with excess LLH₂ from water electrolysis at 8:1 ratio

PS can carry up to ~39.8 t LH₂ in its 7.6 m OD x ~15.7 m L tank. It carries ~20.5 t of LH₂ at TLI




Image Credit: NASA/GRC

“Top off” LLH₂ added to PS before TEI ~6.95 t


In-line LO₂ tank assembly can carry up to ~111.2 t of LO₂ in its 4.6 m OD x ~7.95 m L tank. It carries ~103.5 t of LO₂ at TLI and refuels with ~55.6 t of LLO₂ in LPO before returning to Earth

*Ref: Aerojet Rocketdyne RL10 Engine Specifications – www.rocket.com (March 2019)

*NOTE: 1-way transit times shown do not include the 2.5-hr long, 3-burn LOC maneuver into LPO



Relative Size of the *Conestoga* Crewed Cargo Transport and Passenger Commuter Shuttle



Glenn Research Center

SRR & PTMSS 10th Joint Meeting, Golden, Colorado, June 11 - 14, 2019

Source of Images: NASA/GRC

at Lewis Field



How Might a Typical Commuter Flight to the Moon Proceed?

A possible scenario might start with passengers boarding a future “Earth-to-Orbit” shuttle for a flight to a future commercial artificial gravity station (AGS) located in LEO. There travelers would enter a Passenger Transport Module (PTM) containing its own life support, power, instrumentation and control, and RCS. The PTM provides the “brains” for the LANTR-powered shuttle and is home to the 18 passengers and 2 crewmembers operating it while on route to the Moon. After departing the AGS, the PTM docks with the fully fueled LANTR shuttle awaiting it a safe distance away. At the appropriate time, the shuttle fires its LANTR engines to begin the trip to the Moon.



Glenn Research Center

SRR & PTMSS 10th Joint Meeting, Golden, Colorado, June 11 - 14, 2019



Source of Images: NASA/GRC

at Lewis Field



How Might a Typical Commuter Flight to the Moon Proceed?

After a 1-1.5-day transfer, the LANTR shuttle arrives in LLO where the PTM detaches and docks with a “Sikorsky-style” LLV awaiting it in LLO. After its delivery to the lunar surface, the PTM is lowered to a “flat-bed” surface vehicle and electronically engaged providing the PTM with surface mobility. The PTM then drives itself to the lunar base airlock for docking and passenger unloading. This scenario is reversed on the return trip back to Earth.



Glenn Research Center

SRR & PTMSS 10th Joint Meeting, Golden, Colorado, June 11 - 14, 2019

Source of Images: NASA/GRC

at Lewis Field



LANTR Commuter Shuttle Mission to LPO




Image Credit: NASA/GRC


*NOTE: 1-way transit times shown do not include the 2.5-hr long, 3-burn LOC maneuver into LPO

Glenn Research Center

at Lewis Field




RL10B-2 Commuter Shuttle Mission to LPO



Lunar Water Production Rate, Mining Area, and Electrolysis Power Requirements

To determine the quantities of LDP needed at both the surface mining facility, and the orbital STN, one must look at the different mission types, their transit times, and their frequency of occurrence. The needs of the different LLVs supporting each mission type must also be taken into account.



* Weekly LANTR / RL10B-2 Shuttle flights to LPO, 1-way transits of 33.5 / 36.5hr, 8:1 refuel ratio, LH₂O electrolyzed for Shuttle: 6,376 t; for LLV use: 18,540 t. P_e (MW_e) * ~3.57 at STN; ~10.4 on LS

= Fast LANTR CCT mission delivers 20 t to LPO in 39.2 hr, 8:1 refuel ratio, 12 missions/yr. LH₂O electrolyzed for CCT use: 1,471 t; for LLV use: 4,806 t. P_e (MW_e) * ~0.823 at STN; ~2.69 on LS

Fast RL10B-2 CCT mission delivers 20 t to LPO in 41.7 hr, 8:1 refuel ratio, 12 missions/yr. LH₂O electrolyzed for CCT use: 1,415 t; for LLV use: 4,617 t. P_e (MW_e) * ~0.790 at STN; ~2.58 on LS

x RL10B-2 CCT mission delivers 20 t to LPO in 72 hr, refuels at 8:1 ratio, then returns to LEO. 6 missions/yr assumed. LH₂O electrolyzed for CCT use: 376 t; for LLV use: 1,638 t. P_e (MW_e) * ~0.210 at STN; ~0.92 on LS

+ LANTR CCT mission delivers 20 t to LPO in 72 hr, refuels at 8:1 ratio, then returns to LEO. 6 missions/yr assumed. LH₂O electrolyzed for CCT use: 367 t; for LLV use: 1,584 t. P_e (MW_e) * ~0.205 at STN; ~0.89 on LS

*P_e (MW_e) ~0.2042 x H₂O Electrolysis Rate (t/day)




LANTR Commuter Shuttle Mission to Equatorial LLO uses only LUNOX Refueling for Earth Return

Shortest transit time mission using LUNOX only

(LEO → LLO → LEO)

- **33.1-hr** “1-way” transit times
- Total Mission ΔV ~10.419 km/s
- PTM mass ~15 t
- In-line LO_2 tank element ~117.9 t
- Common LH_2 NTPS ~71.1 t
- **IMLEO ~204 t**
- LANTR engines operate O_2 -rich
Out and Back: MR~5; I_{sp} ~516 s
- **Total Mission Burn Time: ~25.3 min**

NTPS carries ~39.8 t of Earth-supplied LH_2
– sufficient for the round trip mission – in its
7.6 m OD x ~15.7 m L tank



Shuttle's Passenger Transport Module
(PTM) carries 2 pilots and 18 passengers;
OML Dimensions: ~4.6 m D x 8 m L

In-line LO_2 tank assembly can carry up to ~111.2 t of LO_2 in its
4.6 m OD x ~7.95 m L tank. It is filled to full capacity at TLI
and refuels with ~80.3 t of LUNOX before returning to Earth

Glenn Research Center

SRR & PTMSS 10th Joint Meeting, Golden, Colorado, June 11 - 14, 2019

Image Credit: NASA/GRC


at Lewis Field



Total LUNOX Required for “Weekly” Commuter Flights



LANTR Shuttle
Departing LEO
for the Moon



LANTR Shuttle
Headed Home

33.1 Hour “1-Way” Transits (15 t / 20 Person PTM):

LANTR Shuttle: (80.3 t LUNOX /mission/week)
x 52 weeks/year = 4,176 t/yr

LLV** : (33.8 t LUNOX / flight)
x (1 flight/LLV/week) x 4 LLVs x 42 weeks/year = 5,678 t/yr


LLV**# : (49.1 t LUNOX# / round trip flight / week)
x (1 flight/LLV/week) x 52 weeks/year = 2,553 t/yr

Total LUNOX Production = 12,407 t/yr



*O/H MR = 5.5:1, $I_{sp} = 450$ s, $\Delta V_{desc} = 2.115$ km/s & $\Delta V_{asc} = 1.985$ km/s assumed
 *LLV tanker transports ~25 t of LUNOX to LLO; returns to LS with empty 5 t tank
 #Total for LLV delivery of PTM from LLO to LS plus PTM return from the LS to LLO

LLV Unloading PTM onto
a Mobile Surface Vehicle



Tanker LLV Delivering
LUNOX to LLO Depot

Glenn Research Center


Source of Images: NASA/GRC

at Lewis Field



Mining Area and LUNOX Production Rate Required to Support Weekly Commuter Flights to the Moon

The Taurus-Littrow DMD is large (~3000 km²) and is tens of meters thick.



Plant Mining Rate:

- To produce 13,000 t of LUNOX annually requires glass throughput of $\sim 3.25 \times 10^5 \text{ t/yr}$ at $\text{MMR} = 25:1$
- Assuming 13 LUNOX production plants – each producing 1000 t/yr – each plant processes $\sim 2.5 \times 10^4 \text{ t/yr}$
- The mining equipment at each plant includes 2 front-end loaders and 4 haulers
- The mining rate at each plant is just over 4 t per hour per loader based on a 35% mining duty cycle
- Corresponds to mining operations during 70% of the available lunar daylight hours ($\sim 3067 \text{ hours per year}$)
- The power needed for mining and processing per plant is $\sim 2 \text{ MW}_e$

Could supply LUNOX for 25 commuter flights carrying 450 passengers each week for next 2215 yrs!



Total LUNOX Required for “Weekly” Commuter Flights



LANTR Shuttle
Departing LEO
for the Moon



LANTR Shuttle
Headed Home


32.1 Hour “1-Way” Transits (15 t / 20 Person PTM):

LANTR Shuttle: (80.3 t LUNOX /mission/week)
x 52 weeks/year = 4,176 t/yr


LLV** : (33.8 t LUNOX + 6.14 t ELH₂ / flight)
x (1 flight/LLV/week) x 4 LLVs x 42 weeks/year = 5,678 t/yr
+ 1,032 t/yr (ELH₂)

LLV**# : (49.1 t LUNOX# + 8.92 t ELH₂ / round trip flight)
x (1 flight/LLV/week) x 52 weeks/year = 2,553 t/yr
+ 464 t/yr (ELH₂)

Total LUNOX Production = 12,407 t/yr
Total ELH₂ Required 1,496 t/yr



LLV Unloading PTM onto
a Mobile Surface Vehicle




Tanker LLV Delivering
LUNOX to LLO Depot

*O/H MR = 5.5:1, I_{sp} = 450 s, ΔV_{desc} = 2.115 km/s & ΔV_{asc} = 1.985 km/s assumed
*LLV tanker transports ~25 t of LUNOX to LLO; returns to LS with empty 5 t tank
#Total for LLV delivery of PTM from LLO to LS plus PTM return from the LS to LLO



Synergy with an Emerging He-3 Mining Industry


- For ambitious LUNOX architectures, the increasing amounts of ELH_2 required and methods for delivering it to LLO are concerns. A solution to the LH_2 resupply issue is solar-wind-implanted (SWI) volatiles extraction.
- During He-3 mining, significant quantities of lunar volatiles are produced as “by-products”. Eight automated Mark II miners (each producing ~33 kg of He-3 per yr) can supply over 1500 t of LH_2 while also producing ~264 kg of He-3 annually (This is ~95 x smaller than the 25 t/yr discussed previously by Kulcinski & Schmidt).
- The mass, power requirement, annual regolith throughput, excavation rate and area, of each He-3 miner is ~18 t, 200 kW_e, ~5 million tons, 1630 t per hr, and ~1 km², respectively.
- Mare Tranquillitatus has titanium-rich regolith, large surface area (~190,000 km²) and could contain ~7100 t of He-3. To the northwest is Mare Serenitatis, another location for He-3 mining and LUNOX production.
- An alternative to the conventional mining approach is in-situ extraction of lunar soil volatiles. Proposed by Wittenberg in 1994, it has many of the same features as today’s thermal mining approach for water extraction.



(Ref: Kulcinski et al., AIAA-96-0490, 1996)

Gaseous Volatiles Released During Heating of Lunar Ilmenite to 700 C

Isotope Molecule, or Compound	t of Volatile Released per kg of He-3
H ₂	6.1
H ₂ O	3.3
He-4	3.1
CO	1.9
CO ₂	1.7
CH ₄	1.6
N ₂	0.5
Total Volatiles =	18.2



(Ref: L.J. Wittenberg, Space 94, 4th Int. Conf. on Engineering, Construction & Operations in Space, Feb. 26 – Mar 3, 1994, Albuquerque, NM)

Glenn Research Center

at Lewis Field



Summary and Conclusions

- Commercialization and human settlement of the Moon and cislunar space will be greatly aided by the development and utilization of ISRU, FPS, reusable propulsion systems, and the strategic positioning of STNs in LEO, lunar polar and equatorial orbits. Reusable propulsion systems implies long operating lifetimes: hours not minutes.
- Lunar-derived propellants (LDPs) can be extracted from abundant reserves of icy polar regolith, vast volcanic glass deposits on the lunar nearside, and, longer term, from volatile byproducts extracted during He-3 mining.
- The combination of LDP with chemical and LANTR propulsion can lead to a robust LTS with unique mission capabilities that include short transit time, crewed cargo transports and commuter flights to the Moon.
- Chemical propulsion exists now but LANTR propulsion offers some unique features. It provides a variable thrust and I_{sp} capability, has shorter total mission burn times and potentially longer engine life, and allows bipropellant operation. The use of high density LO_2 also leads to smaller LTVs.
- Scalable, megawatt-class FPS can satisfy the requirements for abundant “24/7” electrical power, at low mass, needed for the continued growth of commercial activities in LEO, lunar orbit, and on the lunar surface.
- Besides providing a propellant depot and cargo transfer function, orbiting STNs offer convenient staging locations where propellant, cargo and passengers can be dropped off and/or picked up.
- The biggest challenge to making this vision a reality will be the production of increasing amounts of LDP and the development of STNs in LEO, LLO and LPO. Industry-operated, privately financed ventures, with NASA as its initial customer, might provide a possible blueprint for future development and operation.
- With industry interested in developing cislunar space and commerce, and competitive forces at work, the timeline for developing this capability could well be accelerated beyond anything currently being imagined. Only time will tell, and it may be sooner than any of us can imagine.

Glenn Research Center

at Lewis Field



Backup

Glenn Research Center

SRR & PTMSS 10th Joint Meeting, Golden, Colorado, June 11 - 14, 2019

at Lewis Field




RL10B-2 Commuter Shuttle Mission to Equatorial LLO uses only LUNOX Refueling for Earth Return

Shortest transit time mission using LUNOX only

(LEO → LLO → LEO)

- **31.1-hr** “1-way” transit times
- Total Mission ΔV ~10.966 km/s
- PTM mass ~15 t
- In-line LO_2 tank element ~117.7 t
- Common LH_2 PS ~49.2 t
- **IMLEO ~181.9 t**
- RL10B-2: MR / Isp~ 5.88:1 / 465.5 s
- **Total Mission Burn Time: ~50 min**

PS can carry up to ~39.8 t of Earth-supplied LH_2 in its 7.6 m OD x ~15.7 m L tank. It carries ~32.2 t at TLI



Shuttle's Passenger Transport Module (PTM) carries 2 pilots and 18 passengers; OML Dimensions: ~4.6 m D x 8 m L

In-line LO_2 tank assembly can carry up to ~111.2 t of LO_2 in its 4.6 m OD x ~7.95 m L tank. It is filled to full capacity at TLI and refuels with ~76.5 t of LUNOX before returning to Earth

Glenn Research Center

SRR & PTMSS 10th Joint Meeting, Golden, Colorado, June 11 - 14, 2019

Image Credit: NASA/GRC

at Lewis Field

